

- **Monitor Audio Vector 10 Satellites**

- The Vector 10 is designed primarily for use with the VS20 and VW-8 in an ultra-compact multichannel home cinema package, its unusually deep bass makes it ideal for stereo sound around the home.
- The VS10's compact rear-ported cabinet houses a 100mm (4") MMP II bass driver complemented by a 25mm (1") gold C-CAM dome tweeter to deliver clear highs and punchy bass lines across a frequency response extending from 65Hz to well over 30kHz.
- The magnetically shielded mid/bass driver, protected by a perforated metal grille, makes the VS10 safe for use near sensitive microprocessor equipment or video displays, and from a tabletop or wall location.
- A single point fixing is provided at the rear for easy bracket fixing
- Power Handling (RMS): 50 watts
- System Power Handling (RMS): 90 watts
- Nominal Impedance: 8 ohms
- Recommended Amplifier Requirements: 10 - 80 watts
- Frequency Response: 65Hz - 30kHz
- Dimensions (HxWxD): 235 x 145 x 170 - 2.17kg (each)

- **Monitor Audio Vector 20 Centre**

- The compact V20 is a versatile speaker that can be used horizontally for a centre channel home cinema duties or vertically as a left/right satellite in multichannel or stereo applications around the home.
- Equipped with a 100mm (4") MMP II bass driver and a 25mm (1") gold C-CAM tweeter, the V20 shares the tonal characteristics of the V10, but its larger cabinet gives it the extended bass response necessary for the accurate reproduction of the movie dialogue.
- Its front-ported textured polymer cabinet contrasts stylishly with the lacquer and wood effect finishes of its front baffle to add a fresh contemporary accent to the design.
- Located behind rugged perforated metal grilles, the shielded mid/bass driver gives you the freedom to install the V20 near sensitive video displays.
- A recessed terminal panel and threaded 6.35mm (1/4") insert allows for easy wall installation.
- Power Handling (RMS): 50 watts
- System Power Handling (RMS): 90 watts
- Nominal Impedance: 8 ohms
- Recommended Amplifier Requirements: 10 - 80 watts
- Frequency Response: 60Hz - 30kHz
- Dimensions (HxWxD): 145 x 355 x 170 - 2.66kg

- **Monitor Audio Vector VW-8 Subwoofer**

- The new VW-8 is an ultra-compact but awesomely powerful subwoofer equipped with a potent integral 100 Watt Class A-B amplifier
- The VW-8's rigid, curved and cubic MDF cabinet houses a long-throw 8" driver, which is forward-firing to make the process of positioning the VW-8 as simple and fuss-free as possible.
- Although designed to underpin the Vector series satellites with deep controlled bass frequencies, the VW-8 will integrate beautifully and easily with any compact, high performance home theatre system using the variable volume control, wide ranging crossover adjustments between 45Hz and 150Hz, and its phase switch features.
- Stereo line and LFE inputs allow the VW-8 to contribute a seismic dimension to both music and multichannel movie systems
- For added convenience, the VW-8's signal sensing feature automatically turns it on and off at either end of the performance.
- Low Frequency Limit: 28Hz

- Upper Frequency Limit: 45 - 150Hz (variable)
 - Input Impedance: 20k ohms
 - Low Pass Filter Alignment: 12bD / per octave filter
 - Dimensions (HxWxD): 320 x 280 x 280 - 10.8kg
-